

Pallet Master







Handle pallets at floor level

- > Improve employees' safety
- > Simple and safe pallet handling
- > Reduce pallet damages
- > Tidier storage area
- > Can be adjusted either for EUR or EUR-3 pallets

Pallet Master LP; pneumatically operated

- stack, destack and store pallets in fully automated Pallet Master
- handle pallets at floor level
- made in Finland
- 1 operating mode:
- automatic; stack or destack single pallets at a time
- capacity LP 14 => 15 pallets / 500 kg's or LP 25 => 25 pallets / 1000 kg's
 colour RAL 3020

Connection details:

- 230 V 50 Hz, 10 A
 - ¼" quickclamp connection, 6 bar, max. 120 L/min
- Accessories:
- safety fence for LP 14
- overfilling sensor for safety fence (LP 14)
- Dimensions:
- width 1400/1600 mm (EUR or EUR-3)
- depth 1500 mm
- height 1020 mm
- height with safety fences LP 14: 2320 mm, LP 25: 2830 mm

Air Compressor

- for LP 14 and LP 25
- sound proof encapsulation
- oil free maintenance friendly industrial quality compressor
- 2 pcs power sockets for LP machines
- capacity for running 2 LP machines simultaneously
- includes flexible air hose for LP machine
- colour RAL 3020
- **Connection details:**
- 230 V 50 Hz, 10 A

Dimensions:

- width 450 mm
- length 850 mm
- height 700 mm







Pallet Master LP 14 EL; fully electric

- stack, destack and store pallets in fully automated Pallet Master
- handle pallets at floor level
- made in Finland
- 3 operating modes:
- dispensing; always a pallet dispensed onto the floor level ready for pick up.

filling; always a slot at the floor level ready for entering the pallet automatic; stack or destack single pallets at a time

- capacity LP 14 EL=> 15 pallets / 500 kg's
- colour RAL 3020

Connection details:

• 230 V 50 Hz, 10 A

Accessories:

- safety fence
- overfilling sensor for safety fence

Dimensions:

- width 1400/1600 mm (EUR or EUR-3)
- depth 1500 mm
- height 1020 mm
- height with safety fences: 2320 mm

Pallet Master LP 1.7; fully electric

- stack, destack and store pallets in semi-automated Pallet Master
- handle pallets at floor level
- made in Finland
- 2 operating modes:
- dispensing; required quantity of pallets will be dispensed onto the floor level for pick up. filling; always a slot for max. 7 pallets at the floor level ready for entering the pallets
- start of cycle from OP by operator
- capacity 17 pallets / 700 kg's
- overfilling sensor and safety fences included
- colour RAL 3020

Connection details:

• 230 V 50 Hz, 16 A

Dimensions:

- width 1400/1600 mm (EUR or EUR-3)
- depth 1500 mm
- height with safety fences 2850 mm

Ferroplan – The Best Solution